



TB60T

Rotary draw benders
Max capacity Stainless Steel 60 x 3 mm



machine kit + tooling (former and counterbending die)*

Art.	MACHINE	TUBE	RADIUS	FORMERS
TB60TK2D	TB60T	Gas inches	2 x Ø	Ø 1/2" (21.30 mm), R46 Ø 3/4" (26.90 mm), R56 Ø 1" (33.70 mm), R67 Ø 1 1/4 (42.25 mm), R90 Ø 1 1/2 (48.25 mm), R100 Ø 2" (60.30 mm), R150

Art.	MACHINE	TUBE	RADIUS	FORMERS
TB60TK3D	TB60T	Gas inches	3 x Ø	Ø 1/2" (21.30 mm), R67 Ø 3/4" (26.90 mm), R82 Ø 1" (33.70 mm), R112 Ø 1 1/4 (42.25 mm), R130 Ø 1 1/2 (48.25 mm), R150 Ø 2" (60.30 mm), R190

Art.	MACHINE	TUBE	FORMERS
TB60TKOD	TB60T	OD inches	Ø 5/8" (15.88 mm), R46 Ø 7/8" (22.22 mm), R56 Ø 1" (28.40 mm), R67 Ø 1 1/4 (31.75 mm), R82 Ø 1 1/2 (38.10 mm), R100 Ø 2" (50.80 mm), R150

* Cast iron formers, brass counterbending dies.

FEATURES

- Mild steel tube capacity 60 x 3 mm
- 2" Gas inches (4 mm) capacity
- Square tube capacity 50 x 50 x 3 mm
- Maximum CLR 380 mm
- Simple control with programmable bend angle
- Material spring back compensation with readout
- Quick-change tooling system
- Single Bending Speed
- Accepts Ercolina's A40-P two axis positioning table for multiple and sequential bends
- Optional foot pedal control allows hands-free operation

www.ercolina.com

Rotary Draw benders > TopBender TB60T



TECHNICAL DATA

Flection Modulus	10 cm ³
Minimum Outside Diameter	10 mm - 1/8" Gas
Maximum Shaft Speed	2-4rpm
Maximum Center Line Radius (CLR)	380 mm (optional accessory)
Minimum Center Line Radius (CLR)	10 mm
Power	1.5 kW
Voltage Requirement	400 V 50Hz
Weight	186 Kgs
Dimensions (LxHxW)	500 x 1000 x 760 mm

MAXIMUM CAPACITY

	Material	Max Ø (mm)	Max Thick. (mm)
	Pipe	2" gas	4
	Round tube	60	3
	Soft brass	60	6
	INOX AISI 308	60	3
	INOX AISI 304	60	3
	Welded tube for furniture	60	4
	ST35 hydraulic tube	60	5
	Hard copper & Aluminum	64	6
	Round solids	35	NA
	Rectangular solids	14 x 60	NA
	Rectangular tube	25 X 50	3
	Square tube	50 x 50	3
	Solid square	30 x 30	NA
	Mild steel T	50 x 50	6
	Mild steel C channel	40 x 20	6

capacities based on materials with T.S. 42 Kg/mm² (psi 60.000 Y.P. 25 Kg/mm² (psi 36.000)

CML INTERNATIONAL S.p.A.

Loc. Annunziata, snc 03030 PIEDIMONTE SAN GERMANO (FR) - ITALY
Tel. (+39) 0776 40281 Fax. (+39) 0776 404801
www.ercolina.com info@ercolina.com



by



ERCOLINA WORLDWIDE

Branch offices

CML DEUTSCHLAND GmbH

Ercolina®
Rohr-und Profildiegemaschinen
Remsweg 27
73660 Urbach (GERMANY)
Tel (+49) 07181 872 66
Fax(+49) 07181 872 98
info@cml-deutschland.de
www.ercolina.de

CML USA Inc

3100 Research Parkway
Davenport, Iowa 52806 (USA)
Tel (+1) 563 391 7700
Fax (+1) 563 391 7710
info@ercolina-usa.com
www.ercolina-usa.com

CML ASIA

102-87, Bucheon Technopark 3rd,
36-1 Samjeong-dong Ojeong-gu Bucheon,
Gyeonggi-do (KOREA)
Tel (+82) 32 624 1939
Fax (+82) 32 624 1940
cmlkorea@naver.com
www.ercolina.com